






# COLLECTION: VELVIE

## COLORS: CREMA, MELI

| TECHNICAL DATA  |                            |
|---|----------------------------|
| <b>BASIC INFORMATION</b>  |                            |
| Width   | 138 cm                     |
| Weight  | 360 g/m <sup>2</sup>       |
| Minimum order   | 0.1 m                      |
| Roll length   | 30 m                       |
| <b>ABRASION RESISTANCE</b>  |                            |
| Standard  | EN ISO 12 947-2            |
| Result  | 90 000 martindale cycles   |
| <b>COLOUR FASTNESS TO LIGHT</b>   |                            |
| Standard  | ISO 105-B02                |
| Result  | 3-6                        |
| <b>COLOUR FASTNESS TO RUBBING</b>   |                            |
| Standard  | EN ISO 105 X12             |
| Wet friction  | 4-5                        |
| Dry friction  | 4-5                        |
| <b>COMPOSITION</b>  |                            |
| Polyester   | 100%                       |
| <b>SHRINKAGE</b>  |                            |
| Warp  | 0,5%                       |
| Weft  | 0,11%                      |
| <b>SEAM SLIPPAGE</b>  |                            |
| Standard  | EN ISO 13 936-2            |
| Weft  | 3 mm                       |
| Warp  | 3 mm                       |
| <b>PILLING</b>  |                            |
| Standard  | EN ISO 12 945-2            |
| Result  | 5                          |
| <b>FLAME RETARDANT STANDARDS</b>  |                            |
| Standard  | Result                     |
| EN 1021   | 1*                         |
| Over PU foam  | ** FR 55 kg/m <sup>3</sup> |
| <b>MAINTENANCE</b>  |                            |
|  |                            |




| APPLICATIONS / PARAMETERS      |   |
|--------------------------------|---|
| <b>APPLICATION</b>             |   |
| Upholstery                     |  |
| Decorative                     |  |
| <b>PARAMETERS</b>              |   |
| Oeko-Tex Standard 100 class II |  |
| Protective finish              |  |

# COLLECTION: VELVIE

## COLORS: CREMA, MELI






### TECHNICAL DATA

| BASIC INFORMATION   |                            |
|---|----------------------------|
| Width   | 140 cm                     |
| Weight  | 433 g/m <sup>2</sup>       |
| Minimum order   | 0.1 m                      |
| Roll length   | 40 m                       |
| ABRASION RESISTANCE   |                            |
| Standard  | EN ISO 12 947-2            |
| Result  | >90 000 martindale cycles  |
| COLOUR FASTNESS TO LIGHT  |                            |
| Standard  | EN ISO 105-B02             |
| Result  | 5                          |
| COLOUR FASTNESS TO RUBBING  |                            |
| Standard  | EN ISO 105 X12             |
| Wet friction  | 3-4                        |
| Dry friction  | 4                          |
| COMPOSITION   |                            |
| Polyester   | 100%                       |
| SHRINKAGE   |                            |
| Result  | +/- 1%                     |
| SEAM SLIPPAGE   |                            |
| Standard  | EN ISO 13 936-2            |
| Weft  | 2 mm                       |
| Warp  | 2 mm                       |
| PILLING   |                            |
| Standard  | EN ISO 12 945-2            |
| Result  | 5                          |
| FLAME RETARDANT STANDARDS   |                            |
| Standard  | Result                     |
| EN 1021   | 1*                         |
| Over PU foam  | ** FR 55 kg/m <sup>3</sup> |
| MAINTENANCE   |                            |
|  |                            |

Iron on reverse.



### APPLICATIONS / PARAMETERS

| APPLICATION                    |   |
|--------------------------------|---|
| Upholstery                     |  |
| Decorative                     |  |
| PARAMETERS                     |   |
| Oeko-Tex Standard 100 class II |  |
| Protective finish              |  |
| Teflon                         |  |